

June 21, 2001

Date

Dail
Express Mail Label No.: EL 846162275 US

DESCRIPTION

LIQUID CRYSTAL DISPLAY DEVICE

5 TECHNICAL FIELD

The present invention generally relates to liquid crystal display devices, and, more particularly, to a liquid crystal display device that has liquid crystal sealed between a first
10 transparent substrate and a second transparent substrate.

BACKGROUND ART

In recent years, liquid crystal display
15 devices have been widely used, because of the advantageous features, such as the thinness, lightness, low driving voltage, and low consumption power. Particularly, active-matrix liquid crystal display devices having an active element for each
20 pixel, such as TFT-LCDs (Thin Film Transistor Liquid Crystal Displays) have been becoming comparable with CRTs in terms of display quality.

However, the use of LCDs has been limited due to narrow viewing angle. In order to eliminate
25 this problem, various techniques have been suggested. Among those techniques, there are many techniques in which electrodes are patterned so as to control the inclinations of liquid molecules in various directions by changing the field distribution in
30 cells. However, the electrode patterning techniques cause the problems described later. The present invention can be applied to all the electrode patterning techniques, and easily solve those problems.

35 First, LCDs that are generally used for display devices will be described. At present, the most commonly used LCDs are TN (Twisted Nematic)

LCDs of normally white mode. FIG. 1A shows the panel structure of such a TN-LCD. In FIG. 1A, TN liquid crystal 12 is sandwiched by glass substrates having alignment layers 10 and 11 having orientated directions deviated by 90 degrees from each other. Accordingly, the liquid crystal in contact with the alignment layers 10 and 11 are aligned in the orientated directions of the alignment layers, and the other liquid crystal molecules are orientated along the aligned liquid crystal molecules. As a result, the molecules are twisted through 90 degrees. Further, the liquid crystal and the alignment layers 10 and 11 are sandwiched by two polarizing plates 13 and 14 that are situated in parallel with the orientated directions of the upper and lower portions of the liquid crystal, respectively. When light impinges on the panel having the above structure, the light passing through the polarizing plate 13 turns into linearly polarized light and enters the liquid crystal 12. Along with the liquid crystal 12 twisted through 90 degrees, the light is also twisted through 90 degrees while passing through the lower polarizing plate 14. Here, the display is in a bright state.

As shown in FIG. 1B, a voltage is applied between the alignment layers 10 and 11, thereby straightening the liquid crystal molecules and eliminating the twist. However, on the surfaces of the alignment layers 10 and 11, the liquid crystal molecules remain along the alignment layers 10 and 11 due to the strong orientation force. In this situation, the liquid crystal 12 is almost homeotropic with the linearly polarized light, and no rotation of the polarizing direction occurs. Here, the display is in a dark state. When the voltage is zero, the display returns to a bright state due to the orientation force by the alignment

layers.

Next, an IPS (In-Plane Switching) method that realizes a wider viewing angle will be described. For instance, Japanese Patent No. 53-48452 and Japanese Patent No. 1-120528 disclose methods in which an electric field in parallel with the substrates is generated in liquid crystal layers. As shown in FIG. 2A, according to this method, a pair of striped electrodes 21 and 22 are formed on a substrate 20 on one side, and the liquid crystal molecules located between the slit-like electrodes 21 and 22 are driven by a lateral electric field. The liquid crystal 23 is made of a material having positive dielectric anisotropy. When no electric field is applied, the liquid crystal molecules are homogeneously aligned in parallel with the longitudinal direction of the striped electrodes 21 and 22, as shown in the plan view of FIG. 2B (i.e., the liquid crystal molecules are homogeneously orientated at an angle of approximately 15 degrees, so that the director directions of the liquid crystal molecules become uniform when a voltage is applied).

When a voltage is applied between the striped electrodes 21 and 22, the directors of the liquid crystal molecules having dielectric anisotropy are changed, as shown in FIGS. 3A and 3B. In such a liquid crystal display device, polarizing plates 25 and 26 are arranged on and under substrates 20 and 24, with the polarizing axes or the absorbing axes crossing perpendicularly to each other. One of the polarizing axes is located in parallel director direction, so that a black display can be realized when no voltage is applied and a white display can be realized when a voltage is applied.

There have been dramatic improvements in

the TN-type TFT-LCD production techniques, and, in recent years, the TN-type TFT-LCD production techniques excels CRTs in contrast ratio and color reproducibility. However, the LCDs have a narrow viewing angle. Particularly, a TN-type has only a very narrow viewing angle in the vertical direction. Viewed from some other direction, the brightness of the black state increases, making the image whitish. Viewd from the other direction, the display becomes dark, and gray-scale inversion occurs.

When a voltage is applied to TN liquid crystal cells, the liquid crystal molecules are inclined in some degree. At this point, the birefringence of the liquid crystal layer makes the cells have a gray scale transmittance. However, this is the case only when the liquid crystal panel is seen from the front, and the liquid crystal panel looks different when it is seen from an oblique angle. In FIG. 4, the appearance seen from the left is different from the appearance seen from the right. For instance, the liquid crystal has little birefringence effect on the light directed from the lower left to the upper right in FIG. 4. Accordingly, when seen from the right, the panel looks black, not gray. On the other hand, with the light passing from the lower right to the upper left, the birefringence effect becomes larger. As a result, the display looks even whitish and closer to white.

To solve this problem, it is effective to employ the technique of multidomain. According to this technique, a plurality of inclined directions of the liquid crystal molecules exist in one pixel. Because of this, the left half of the pixel in FIG. 5 exhibits a large birefringence for the light passing from the lower left to the upper right (white display), and the right half of the pixel

exhibits little birefringence (white display). In such a condition, the display appears to be a gray scale image to a human eye, as long as the division size is small enough. When seen from the left, the display appears to be gray for the same reason. From seen from the front, the display of course appears to be gray because the inclined angles of the liquid crystal molecules are uniform on both left and right sides. Thus, uniform gray scale image can be obtained throughout a wider viewing angle range.

To achieve a multidomain structure, a mask rubbing process shown in FIG. 6 can be used. When an alignment layer is rubbed with a rubbing roller made of nylon or polyester, the liquid crystal molecules have tendency to be orientated in the rubbing direction. Taking advantage of this tendency, alignment layers 32 and 33 of substrates 30 and 31 are subjected to rubbing in the right direction by rubbing rollers 34 and 35, as shown in FIG. 6A. Next, a half of each pixel is subjected to masking with resists 36 and 37, as shown in FIG. 6B. The alignment layers 32 and 33 are then subjected to rubbing in the left direction, as shown in FIG. 6C. The resists 36 and 37 are then removed, and the substrates 30 and 31 are attached to each other, with liquid crystals inside, thereby completing a liquid crystal cell having the left and right orientation directions.

With the mask rubbing method, however, there exist many problems. These problems include the low productivity due to the complicated process, the limitation on the number of divisions (at least four divisions are necessary to satisfy all the conditions with respect to contrast, color, and gray scale, but the maximum number of divisions is 2 because of the complicated process), and poor

controllability in the rubbing process due to the masking process. For these reasons, it has been very difficult to mass-produce the multidomain panels by the mask rubbing process.

5 Other techniques to solve the above problems and to achieve a wider viewing angle include a method in which an electric field distortion is caused in a cell so as to control the alignments. However, there are other problems in
10 this case, such as the difficulty in patterning electrodes, poor yield, and higher costs due to a larger number of processes. Furthermore, if a minutely striped electrode is formed from an ITO (indium tin oxide) layer, a voltage drop is caused
15 at the end portion of the electrode, resulting in display unevenness.

 In the IPS method, the liquid crystal are switched in the horizontal direction. As mentioned before, when the liquid crystal molecules are
20 aligned with an inclined angle to the substrates, the birefringence varies with the viewing angle direction. The switching is carried out in the horizontal direction so as to steady the birefringence and obtain excellent viewing angle
25 characteristics. However, this method also causes several problems. First of all, the response is very slow, because the switching is carried out with an electrode gap of about 10 μm in the IPS method, compared with the switching with an electrode gap of
30 about 5 μm in the conventional TN method. The response time can be shortened by narrowing the electrode gap, but each two adjacent electrodes needs to have an different electrical potential to apply an electrical field. Otherwise, short-
35 circuiting will be easy to occur between the adjacent electrodes, resulting in display with defects. To avoid such a problem, each two adjacent

electrodes are formed on two different layers, but this simply increases the number of manufacturing processes.

Also, since it is difficult to form
5 minutely striped electrode with ITO, striped metal electrodes are employed instead. However, this causes a loss in the aperture ratio. If the pitch of the striped electrode is narrowed to increase the response speed, the proportion of the electrode to the total area becomes large, resulting in lower
10 transmittance. (In reality, the transmittance of the IPS method is only two thirds of the transmittance of the TN method. If the electrode pitch is halved and the density of the striped
15 electrode is doubled, the transmittance becomes only one third of the transmittance of the TN method.) Because of the above reasons, the similar display quality (in terms of brightness) cannot be obtained, unless the brightness of the backlight is tripled,
20 for instance.

In reality, when quickly moving dynamic images are displayed, blurring occurs in the images. Further, to increase the response speed, a panel is subjected to rubbing not in the direction of the
25 electrode but in the direction deviated by for example about 15 degrees from the direction of the electrode. If the rubbing is performed in the direction of the electrode, the rotational direction of the liquid crystal molecules in the middle of the electrodes is not stabilized as one direction,
30 resulting in a longer response time. Therefore, by inclining the rubbing direction by 15 degrees, even after this process, the response time is twice that of the TN type. Through this process, the viewing
35 angle characteristics are not perfectly symmetric, and some gray-level inversion occurs around the rubbing direction.

To explain this situation, the coordinate system of a polar angle θ shown in FIG. 7A and the azimuth angle ϕ shown in FIG. 7B are determined for the substrates 20 and 24, the electrodes 21 and 22, and the liquid crystal molecules 23 shown in FIGS. 7A and 7B. FIG. 8A shows the viewing angle characteristics of the panel, in which the gray scales are divided into eight levels from the white state to the black state, and the brightness variations are analyzed by varying the polar angle and the azimuth angle. The shadowed portions in the figure represent gray-level inversion, which are caused in the two azimuths (the 45-degree ranges of 60 to 105 degrees and 240 to 285 degrees in the azimuth angle ϕ). FIG. 8B shows the transmittance variations of the 8 gray-level displays with respect to the polar angle θ at an azimuth angle of 75 degrees, which causes inversion. The gray-level inversion is caused due to a drop in the white brightness.

In the IPS method, the gray-level inversion is caused due to a drop in the white brightness in the two azimuths, and the viewing angle characteristics deteriorate. By switching in the lateral direction, viewing angle characteristics equivalent to a multidomain panel, but the transmittance, the response speed, the productivity and the market price are all sacrificed. Particularly, a low response speed is not suitable for displaying dynamic picture images.

DISCLOSURE THE INVENTION

The principal object of the present invention is to provide a liquid crystal display device that exhibits improved viewing angle characteristics, restricts gray-level inversion, and has a short response time.

To achieve the above object, the present invention provides a liquid crystal display device that has a pair of substrates having electrodes facing each other, and has liquid crystal sealed between the substrates. The device includes an insulating layer that varies electric field orientations in a pixel region when a voltage is applied between the pair of substrates. Accordingly, the liquid crystal molecules become perpendicular to the lines of electric force (in a case of negative liquid crystal) or in parallel with the lines of electric force (in a case of positive liquid crystal). Because of the varied orientations of the electric force, a brightness variation becomes smaller when seen from any direction, and the viewing angle characteristics are improved. Furthermore, gray-level inversion can be restricted.

BRIEF DESCRIPTION OF THE DRAWINGS

The other objects, features, and advantages of the present invention will become more apparent from the following description, with reference to the accompanying drawings.

FIG. 1 shows the structure of a TN-type LCD panel;

FIG. 2 shows the structure of an IPS-type LCD panel;

FIG. 3 shows the structure of the IPS-type LCD panel;

FIG. 4 illustrates the viewing angle dependence with a conventional device;

FIG. 5 illustrates a conventional multidomain structure and the viewing angle dependence;

FIG. 6 illustrates a mask rubbing method;

FIG. 7 illustrates the definition of polar angle θ and azimuth angle ϕ ;

FIG. 8 illustrates gradation inversion;

FIG. 9 is a sectional view illustrating the principles of the present invention;

FIG. 10 illustrates the movement of liquid crystal molecules at a time of voltage application;

FIG. 11 shows a zigzag pattern of a transparent insulating film;

FIG. 12 illustrates the viewing angle characteristics of a device in accordance with the present invention;

FIG. 13 shows the viewing angle characteristics of a conventional device (TN);

FIG. 14 shows the viewing angle characteristics of the device in accordance with the present invention;

FIG. 15 is a sectional view of a first embodiment of a liquid crystal display device in accordance with the present invention;

FIG. 16 is a plan view of the first embodiment of the liquid crystal display device in accordance with the present invention;

FIG. 17 is a perspective view of transparent insulating films and transparent electrodes;

FIG. 18 illustrates a situation when a voltage is applied between the transparent electrodes;

FIG. 19 shows the relationship between the applied voltage and light transmittance;

FIG. 20 shows a response time when the applied voltage is changed;

FIG. 21 shows a microscopic pictures of a test cell when the voltage is variable;

FIG. 22 shows a microscopic pictures of a different test cell when the voltage is variable;

FIG. 23 shows a microscopic pictures of a yet another test cell when the voltage is variable;

FIG. 24 illustrates a modification of the sectional structure of the present invention;

FIG. 25 is a plan view showing a modification of the transparent insulating film in accordance with the present invention related to the modification shown in FIG. 24;

FIG. 26 is an exploded perspective view of a modification of the present invention;

FIG. 27 shows the viewing angle characteristics of the present invention; and

FIG. 28 shows the viewing angle characteristics of the prior art.

PREFERRED EMBODIMENTS FOR CARRYING OUT THE INVENTION

The following is a description of embodiments of the present invention, with reference to the accompanying drawings.

FIGS. 9A, 9B, and 9C are sectional views for illustrating the principles of the present invention.

In FIG. 9A, an upper ITO electrode 40 faces a lower ITO electrode 42, with a space being maintained between the two electrodes 40 and 42, so that liquid crystal 44 is sealed between the two electrodes 40 and 42. A transparent insulating film 46 as a dielectric insulating layer is formed on the lower ITO electrode 42. A vertical alignment layer (not shown) is formed between the liquid crystal 44 and the upper ITO electrode 40 and between the liquid crystal 44 and the ITO electrode 42 (or the transparent insulating film 46).

In the structure shown in FIG. 9A, one transparent insulating film 46 substantially covers the most part of one pixel. The broken lines indicate the lines of electric force when a voltage is applied between the ITO electrodes 40 and 42. Because of the insulating film 46 (preferably

transparent), the lines of electric force inclines in the direction perpendicular to the ITO electrode 40.

When no voltage is applied between the ITO electrodes 40 and 42, the liquid crystal molecules 45 of the liquid crystal 44 is orientated perpendicularly to the surface of the ITO electrode 40, as shown in FIG. 10A. FIG. 10 shows a vertical alignment layer 50 on the side of the transparent insulating films 46. When a voltage is applied between the ITO electrodes 40 and 42, the liquid crystal molecules 45 which are not covered with the transparent insulating films 46 start inclining along the inclination of the lines of electric force, as shown in FIG. 10B. If the applied voltage rises, the liquid crystal molecules 45 located at the transparent insulating films 46 start inclining, as shown in FIG. 10C. The liquid crystal molecules 45 then go through the stage shown in FIG. 10D. When the applied voltage becomes high enough, all the liquid crystal molecules 45 lie in almost parallel with the surface of the ITO electrode 40 while actually being orientated perpendicularly to the lines of the electric force.

By forming the insulating (preferably transparent) films 46 that varies the orientations of the electric field in a pixel region, the liquid crystal molecules become perpendicular to the lines of electric force by the voltage application. The orientations of the electric field vary, and a plurality of gradient orientations exist for the liquid crystal. As a result, the brightness variation becomes smaller over a wide range of viewing angles, and the viewing angle characteristics improve. Also, the occurrence of gradation inversion can be restricted.

In FIG. 9B, the upper ITO electrode 40

faces the lower ITO electrode 42, with a space being maintained, and the liquid crystal 44 is sealed therebetween. The transparent insulating films 46 are formed on the lower ITO electrode 42, while
5 transparent insulating films 48 are formed on the upper ITO electrode 40. The transparent insulating films 48 are formed in a staggered state with respect to the transparent insulating films 46. An alignment layer (not shown) is formed between the
10 liquid crystal 44 and the ITO electrode 40 (or the transparent insulating films 48) and between the liquid crystal 44 and the ITO electrode 42 (or the transparent insulating films 46).

In FIG. 9B, each one transparent
15 insulating film 46 covers the most part of one pixel. The broken lines indicate the lines of the electric force created when a voltage is applied between the ITO electrodes 40 and 42. Because of the transparent insulating films 46 and 48, the lines of
20 electric force incline in the direction perpendicular to the ITO electrode 40.

In this manner, the transparent insulating films 46 formed on one substrate are located in a staggered state with respect to the transparent
25 insulating films 48 formed on the other substrate, so that the orientations of the electric field can greatly vary in the pixel region when a voltage is applied between substrates.

In FIG. 9C, the upper ITO electrode 40
30 faces a lower striped ITO electrode 43, with a space being maintained, and the liquid crystal 44 is sealed between the upper ITO electrode 40 and the lower ITO electrode 43. The insulating film 48 facing the striped ITO electrode 43 is formed on the
35 upper ITO electrode 40. A horizontal alignment layer (not shown) is formed between the liquid crystal 44 and the ITO electrode 40 (or the

insulating film 48) and between the liquid crystal 44 and the striped ITO electrode 43.

In FIG. 9C, one single transparent insulating film 48 covers the most part of one pixel. The broken lines in FIG. 9C indicate the lines of electric force caused when a voltage is applied between the ITO electrodes 40 and 43. Because of the insulating film 48, the lines of electric force incline in the direction perpendicular to the ITO electrode 40.

Since the transparent insulating film 48 is formed only one of the substrates while the other substrate is formed by the narrow striped ITO electrode 43, the orientations of the electric field in the pixel region can be greatly varied.

As shown in FIGS. 9A, 9B, and 9C, according to the technique of patterning insulating structures such as the transparent insulating films 46 and 48 to pixels, the insulating structures are not restricted by the pitch of the pixels, and a pattern can be constantly formed with the optimum width and pitch for the orientation of the liquid crystal. Furthermore, the insulating patterns do not need to be joined to one another, but can be independent of one another, allowing more freedom in design.

In the structure shown in FIG. 9B, the liquid crystal 44 is made of a negative nematic liquid crystal, such as MJ961213' (manufactured by Merck & Co. Inc.), and the alignment layers are made of a vertical alignment layer, such as JALS-684 (manufactured by JSR Corporation). The width of the transparent insulating films 46 and 48 is 55 μm , and the gap between the transparent insulating films 46 and 48 is 5 μm . In this case, no rubbing process is performed on the alignment layers, still, excellent liquid crystal orientation can be obtained, and no

display unevenness occurs.

In the structure shown in FIG. 9B, the transparent insulating films 46 and 48 are striped, as shown in FIG. 11, and bent at 90 degrees by every predetermined length in a zigzag pattern. The display characteristics of such a case were measured, and the viewing angle characteristics shown in FIG. 12 were obtained. The viewing angle characteristics shown in FIG. 12 were far better than the viewing angle characteristics of the conventional TN liquid crystal shown in FIG. 13.

In this manner, when the striped insulating layers are zigzag-patterned, the electric field orientations are varied with a voltage applied between the substrates. Further, the viewing angle characteristics are improved, and the gray level inversion is limited.

Although the gap width of the pattern is 5 μm and the pattern width is 55 μm , no display unevenness due to a voltage drop is found, and an excellent image display is obtained. In FIGS. 12 and 13, CR indicates the value of contrast.

In the structure shown in FIG. 9C, the liquid crystal 44 is made of a nematic liquid crystal material with a positive dielectric constant, such as ZLI-4792 (manufactured by Merck Co. Inc.), and the alignment layers are made of horizontal alignment layer, such as AL-1054 (manufactured by JSR Corporation). The width of the striped ITO electrode 43 is 5 μm , the width of the transparent insulating films 46 and 47 is 55 μm , and the gap between the transparent insulating films is 5 μm . In this structure, a rubbing process in the longitudinal direction of the striped ITO electrode 43 was performed on the horizontal alignment layer to obtain the viewing angle characteristics shown in FIG. 14.

In the above embodiment, the present invention is applied to a transmission type.

However, it should be understood that the present invention may also be applied to a reflective

5 display. Either one of the electrodes 40 and 42 of any of the structures shown in FIGS. 9A, 9B, and 9C can be made of metal, and the metal electrode can be used as a reflecting plate, thereby obtaining a reflection-type panel.

10 FIG. 15 is a sectional view of a first embodiment of a liquid crystal display device of the present invention. FIG. 16 is a plan view of the structure of the first embodiment. This embodiment corresponds to the structure shown in FIG. 9C. In
15 FIG. 15, RGB color filters 62, 63, and 64 are formed separately from each other by black matrixes on one surface of the glass substrate 60. A transparent electrode (ITO electrode) 68 is formed on each of the color filters 62, 63, and 64. Further,
20 transparent insulating films 70, 71, and 72 are formed separately from each other on the transparent electrode 68 on each color filter.

Meanwhile, the transparent electrodes (or metal electrodes) 76, 77, and 78 are formed on one
25 surface of the glass substrate 74, facing the transparent insulating films 70, 71, and 72. Also, a data bus line 79 is formed to face each corresponding one of the black matrixes 66. Liquid crystal 80 is sealed between the glass substrates 60
30 and 74.

A shown in FIG. 16, the gate of a TFT 82 is connected to a gate bus line, the source of the TFT 82 is connected to the data bus line 79, and the drain of the TFT 82 is connected to the transparent
35 electrode 68. In this manner, the transparent insulating films 70, 71, and 72 are formed independently of each other, so as to facilitate the

injection process of liquid crystal when the liquid crystal is charged between the facing glass substrates.

FIG. 17 is a perspective view of the transparent insulating films 70 and 71, and the transparent electrodes (or the metal electrodes) 76 and 77. In FIG. 17, the structure is shown upside-down, compared with the structure shown in FIG. 15. However, the horizontal alignment layers formed on the side of the transparent insulating films 70 and 71 are subjected to rubbing in the direction of the arrow in the figure, while the horizontal alignment layers formed on the side of the transparent electrodes 76 and 77.

FIG. 18 illustrates a situation in which a voltage of 5 V is applied between the transparent electrode 68 and the transparent electrodes 76 and 77. In this figure, the narrow solid lines indicate equipotential surface that represents the electric field distribution. The circles indicate liquid crystal molecules, and the circles with wedges indicate the inclination of the liquid crystal molecules due to the electric field. The thick solid lines indicate the light transmittance with the inclination of the liquid crystal molecules.

FIG. 19 shows the relationship between the light transmittance and the voltage applied between the transparent electrode 68 and the transparent electrodes 76 and 77. Here, the horizontal alignment layer is made of AL3506, and the liquid crystal is made of positive nematic liquid crystal, ZLI-4792 (manufactured by Merck & Co. Inc.).

FIG. 20 shows each response time [msec] in cases where the applied voltage is changed from 0 V to 2 V, 0 V to 4 V, 0 V to 6 V, 0 V to 8 V, and 0 V to 10 V. In this figure, each circle indicates a turn-on response time (a change from black to white),

each triangle indicates a turn-off response time (a change from white to black), and each square indicates a total turn-on and turn-off response time. Here, the longest total response time is 90 msec or shorter, and the shortest total response time is approximately 50 msec. This is an improvement, compared with the case of an IPS in which the longest total response time is 100 msec or longer, and the quickest total response time is 60 msec.

FIGS. 21A to 21D illustrate display conditions in cases where the width of each of the transparent electrodes 76, 77, and 78 is 3 μm , the gap among the transparent electrodes 76, 77, and 78 is 6 μm , and the applied voltage among the transparent electrodes 76, 77, and 78 is changed from 3.0 V to 5.0 V to 8.0 V to 10.48 V. FIGS. 22A to 22D illustrate display conditions in cases where the width of each of the transparent electrodes 76, 77, and 78 is 5 μm , the gap among the transparent electrodes 76, 77, and 78 is 10 μm , and the applied voltage among the transparent electrodes 76, 77, and 78 is changed from 3.0 V to 5.0 V to 8.0 V to 10.48 V. FIGS. 23A to 23D illustrate display conditions in cases where the width of each of the transparent electrodes 76, 77, and 78 is 7.5 μm , the gap among the transparent electrodes 76, 77, and 78 is 15 μm , and the applied voltage among the transparent electrodes 76, 77, and 78 is changed from 3.0 V to 5.0 V to 8.0 V to 10.48 V.

The liquid crystal is generally driven by alternating current waveform, but with an improvement in the response speed, it is necessary to take into consideration the influence in 1 frame (in which a direct current is supplied), i.e., the influence from the direct current waveform. Accordingly, the driving characteristics of the liquid crystal show both the alternating current

characteristics and the direct current characteristics. Therefore, the conditions of both characteristics need to be satisfied.

In view of this, the transparent
5 insulating films 46 and 48 employed to exert a
desired influence on the driving characteristics of
the liquid crystal need to be set under
predetermined conditions. More specifically, the
transparent insulating films 46 and 48 need to be
10 set in such a manner as to lower the electric field
either in terms of the alternating current
characteristics or the direct current
characteristics. In terms of the direct current
characteristics, the specific resistance ρ needs to
15 be high enough to exert an influence on the
resistance of the liquid crystal layer. In other
words, to set a value equivalent to or higher than
the specific resistance of the liquid crystal (for
instance, the liquid crystal for TFT driving is 10^{12}
20 Ωcm or higher), the specific resistance ρ needs to
be 10^{12} Ωcm or higher, and more preferably, 10^{13} Ωcm
or higher.

In terms of the alternating current
characteristics, the transparent insulating films 46
25 and 48 need to have the capacity values (which are
determined from the dielectric constant ϵ and the
sectional area) equal to or lower than the capacity
value of the liquid crystal 44 (i.e., a value equal
to or higher than one tenth as an impedance).

30 Accordingly, the influence on the electric
field distribution can be obtained, as well as the
effects in the shape formed by the inclined surfaces
of the transparent insulating films 46 and 48. Thus,
more stable and rigid alignments can be achieved.
35 The liquid crystal molecules that are aligned
vertically in this situation stably exist and act as
separation walls for the domains generated on both

sides. When a higher voltage is applied, the liquid crystal in the transparent insulating films also start inclining. However, the domains formed on both sides of the transparent insulating films 46 and 48 act as partition walls for the liquid crystal molecules on the transparent insulating films 46 and 48, and the liquid crystal in the center of the multidomain incline in the direction substantially in parallel with the stripes of the transparent insulating films 46 and 48, thereby obtaining a very firm orientation. To realize such a situation, the capacity value of the transparent insulating films 46 and 48 in the multidomain needs to be equal to or smaller than 10 times the capacity value of the liquid crystal 44. Accordingly, the material for the transparent insulating films 46 and 48 should preferably have a small dielectric constant ϵ and a large film thickness. More specifically, the dielectric constant ϵ may be approximately 3, and the film thickness of the insulating films may be 0.1 μm or larger. With an even smaller dielectric constant ϵ and thicker insulating films, more preferable functions and effects can be obtained. In this embodiment, a novolak resist having the dielectric constant ϵ of 3 and having protrusions of 1.5 μm in film thickness were used for the aligned multi domain creation. As a result of this observation, it was found that a very stable alignment was achieved. With such insulating films being employed for the insulating films 46 and 48 on both sides, further preferable functions and effects can be obtained. Besides the novolak resist, an acrylic resist ($\epsilon = 3.2$) was measured, and the obtained results were substantially the same as in the case of the novolak resist.

Next, modifications of the sectional structures shown in FIGS. 9A and 9B will be

described. FIG. 24A shows a sectional structure similar to the structure shown in FIG. 9A. Vertical alignment layers 50 and 52 are shown in FIG. 24A. In a modification shown in FIG. 24B, the transparent insulating films 46 made of SiN or the like are uniformly formed on the ITO electrode 42. After that, processes such as ultraviolet ray irradiation on a shadowed portion 47 that is a part of the transparent insulating film 46, thereby making the dielectric constant of the shadowed portion 47 smaller than the dielectric constant ($\epsilon = 3$) of the transparent insulating films 46. By doing so, the lines of electric force at the time of voltage application is bent in the same manner as in FIG. 9A.

In the modification shown in FIG. 24C, the transparent insulating films 46 having thick portions 46A and thin portions 46B are formed on the ITO electrode 42, and the lines of electric force at the time of voltage application is bent in the same manner as in FIG. 9A. In the modification shown in FIG. 24D, the transparent insulating films 46 are not formed on the ITO electrode 42, but a vertical alignment layer 52 having thick portions 52A and thin portions 52B is formed directly on the ITO electrode 42. The lines of electric force at the time of voltage application is bent in the same manner as in FIG. 9A, in accordance with the locations of the transparent insulating films 46 shown in FIG. 24A.

As shown in FIG. 25 by shadowed portions, two transparent insulating films 46 are formed for each one pixel, extending in parallel with the gate bus line 90. Further in FIG. 25, the gate of each TFT 94 is connected to the gate bus line 90, the source of each TFT 94 is connected to the data bus line 92, and the drain of each TFT 94 is connected to the ITO electrode 40.

As shown in FIG. 26, the glass substrates 60 and 62 having the ITO electrodes 40 and 42 and the vertical alignment layers 50 and 25 formed thereon face each other, with a predetermined space being maintained by a spacer. The liquid crystal is then sealed between the glass substrates 60 and 62. The polarizing plates 64 and 66 are arranged in such a manner that the absorption axes cross each other at an angle of 90 degrees.

Here, the vertical alignment layer 52 formed on a color filter is produced by transfer-printing and baking a vertical orientation material, JALS-204 (manufactured by Japan Synthetic Rubber, Co., Ltd.). The transparent insulating films 46 on the side of the TFTs 94 are produced by transfer-printing, exposing, developing and then patterning a photosensitive polyimide material. The vertical alignment layer 50 is produced by transfer-printing and baking a vertical alignment material JALS-204 (manufactured by Japan Synthetic Rubber, Co., Ltd.). The glass substrates 60 and 62 are attached to each other, with a spacer having a diameter of 3.5 μm being interposed therebetween. A negative liquid crystal having a negative dielectric anisotropy is then sealed between the glass substrates 60 and 62.

The angle regions having gray-level inversion in this case are represented by the shadowed portions in FIG. 27. The angle regions having gray-level inversion in the conventional TN-type liquid crystal display device are represented by the shadowed portions in FIG. 28. From FIGS. 27 and 28, it is apparent that the angle regions having gray-level inversion are much smaller in this embodiment.

Since the liquid crystal has the negative dielectric anisotropy, a transparent film having optically negative uniaxial properties in the normal

film direction (which satisfies the equation $N_x \approx N_y > N_z$, where N_x and N_y represent the refractive factor in the direction of the in-plane of the film, and N_z represents the refractive factor in the direction of the normal direction of the film) is attached to either one of the glass substrates 60 and 62, so as to compensate the optical state at the time of non-voltage application (black display). Thus, the viewing angle characteristics can be further improved. Also, an optically biaxial phase difference film ($N_x > N_y > N_z$) or an optically uniaxial phase difference film ($N_x > N_y \approx N_z$) having positive uniaxial properties in the in-plane of the film may be laminated.

In this manner, in a liquid crystal display device having liquid crystal sealed therein, an insulating layer is formed in a region that is narrower than a pixel region. When a voltage is applied between the pair of substrates, the insulating layer varies the orientations of the electric field in the pixel region. In this structure, when a voltage is applied between the pair of substrates, the liquid crystal molecules become perpendicular to the lines of electric force (in a case of negative liquid crystal) or are located in parallel with the lines of electric force (in a case of positive liquid crystal). Accordingly, the orientations of the electric field vary, and a plurality of inclined orientations exist in the liquid crystal. As a result, a brightness variation becomes smaller when seen from any direction, and the viewing angle characteristics are improved. Thus, gray-level inversion can be restricted.

Also, each insulating layer may have a dielectric constant that is different from that of the surrounding area. Thus, the orientations of the electric field in a pixel region can be varied when

a voltage is applied between the pair of substrates.

Further, each insulating layer may have a dielectric substance that has a different thickness from the surrounding area. Thus, the orientations of the electric field in a pixel region can be varied when a voltage is applied between the pair of substrates.

Also, each of the substrates may be provided with an insulating layer in such a manner that the insulating layer formed on one of the substrates is in a staggered arrangement with the insulating layer formed on the other one of the substrates. Thus, the orientations of the electric field can be greatly varied when a voltage is applied between the pair of substrates.

Furthermore, each of the substrates may be provided with a vertical alignment layer, and the liquid crystal may be made of a nematic liquid crystal material with a negative dielectric constant. In this structure, when a voltage is applied between the pair of substrates, the liquid crystal molecules become perpendicular to the lines of electric force, and a plurality of inclined orientations exist in the liquid crystal due to the variation of the orientations of the electric field. Accordingly, a brightness variation becomes smaller when seen from any direction, and the viewing angle characteristics can be improved. Thus, gray-level inversion can be restricted.

Also, an insulating layer may be formed on only one of the substrates, and the electrodes of the other one of the substrates is made narrower than the insulating layer. Thus, the orientations of the electric field in a pixel region can be greatly varied.

Furthermore, each of the substrates may be provided with a horizontal alignment layer, and the

liquid crystal may be made of a nematic liquid crystal material with a positive dielectric constant. In this structure, when a voltage is applied between the pair of substrates, the liquid crystal molecules
5 are situated in parallel with the lines of electric force, and a plurality of inclined orientations exist in the liquid crystal due to the variation of the orientations of the electric field. Accordingly, a brightness variation becomes smaller when seen
10 from any direction, and the viewing angle characteristics are improved. Thus, gray-level inversion can be restricted.

Also, the electric resistivity ρ of each insulating layer may be made higher than the
15 electric resistance of the liquid crystal. Thus, a desired influence can be expected on the electric field distribution of the liquid crystal layer in terms of the direct current characteristics.

Furthermore, the electrode of one of the
20 substrates may be made of metal and serves as a reflecting plate. Thus, a reflection-type display can be obtained.

Also, each insulating film may be a vertical alignment layer that has a thickness
25 different from the surrounding area. Thus, the orientations of the electric field in a pixel region can be greatly varied when a voltage is applied between the pair of substrates.

Furthermore, the impedance of each
30 insulating layer may be equal to or higher than the impedance of the liquid crystal. Thus, a desired influence can be exerted on the electric field distribution in the liquid crystal layer in terms of the alternating current characteristics.

Also, each striped insulating layer may be
35 zigzag-patterned by 90 degrees by the predetermined length. Accordingly, the orientations of the

electric field can be further varied when a voltage is applied between the pair of substrates, and the viewing angle characteristics can be further improved. Thus, gray-level inversion can be

5 restricted.

Also, a plurality of insulating layers may be formed independently of one another, thereby facilitating the injection process of the liquid crystal between the substrates.

10

1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2